



CONTAINER SPECIFICATION

All weight and dimensions are for guidance only – varies from steamship line to steamship line.

TYPE	HEIGHT	TARE WGT	MAX CARGO	DOOR OPENING		INTERIOR DIMENSIONS			INTERNAL CUBE
				WIDTH	HEIGHT	LENGTH	WIDTH	HEIGHT	
20' DRY	8'6"	2200 KGS 4850 LBS	21800 KGS 48060 LBS	2341MM 7'8"	2280MM 7'5"	5898MM 19'4"	2350MM 7'8"	2392MM 7'10"	33.2M ³ 1172 CFT
40' DRY	8'6"	3700 KGS 8160 LBS	26780 KGS 59040 LBS	2341MM 7'8"	2280MM 7'5"	12032MM 39'5"	2350MM 7'8"	2392MM 7'10"	67.6M ³ 2390 CFT
40' H/C	9'6"	3970 KGS 8750 LBS	26510 KGS 58450 LBS	2338MM 7'8"	2585MM 8'5"	12032MM 39'5"	2350MM 7'8"	2697MM 8'10"	76.3M ³ 2694CFT
45'DRY	9'6"	4570 KGS 9981 LBS	25910 KGS 56587 LBS	2338MM 7'8"	2585MM 8'5"	13557MM 44'5"	2352MM 7'8"	2694MM 8'10"	85.9M ³ 3035CFT
20' Reefer	8'6"	3200 KGS 7040 LBS	20800 KGS 45760 LBS	2258MM 7'5"	2216MM 7'3"	5425MM 17'8"	2275MM 7'5"	2260MM 7'5"	28.3M ³ 1000CFT
40' Reefer	8'6"	4900 KGS 10780 LBS	25580 KGS 56276 LBS	2282MM 7'5"	2155MM 7'	11493MM 37'8"	2270MM 7'5"	2197MM 7'2"	57.8M ³ 2040CFT
40' REEFER H/C	9'6"	4500 KGS 9900 LBS	25980 KGS 57561 LBS	2294MM 7'6"	2440MM 8'	11557MM 37'11"	2294MM 7'6"	2500MM 8'2"	66.6M ³ 2344CFT
20' OT	-	2400 KGS 5280 LBS	21600 KGS 47620 LBS	2286MM 7'6"	2184MM 7'2"	5894MM 19'4"	2311MM 7'7"	2286MM 7'8"	32.23M ³ 1136CFT
40' OT	-	3850 KGS 8490 LBS	26630 KGS 58710 LBS	2345MM 7'8"	2274MM 7'5"	12038MM 39'5"	2345MM 7'8"	2345MM 7'8"	65.5M ³ 2350CFT